



**KOMBI 300  
410-500**



COMBINATA A 6 OPERAZIONI  
 COMBINED AT 6 OPERATIONS  
 COMBINÉE À 6 OPERATIONS  
 6 FACH KOMBINIERTE MASCHINEN  
 COMBINADA 6 OPERACIONES

**KOMBI 300/410/500**  
 COMBINATA A 6 OPERAZIONI

COMBINED AT 6 OPERATIONS • COMBINÉE À 6 OPERATIONS  
 6 FACH KOMBINIERTE MASCHINEN • COMBINADA 6 OPERACIONES

Doti speciali  
 Technical data  
 Datos técnicos

Piùla a filo Surfacer planer Degaussolseuse Abdeckschleifmaschine Cepiladora	Dim. piani Tables dim. Dm. tables	Tischh. Dim. meas	300	410	500
▶ a riburo porta collanti ▶ Spindle glue ▶ a arbre porte colantoux		Hohelwelle a eye porta carilhas	70	72	110
▶ Giri/min. albero Spindle speed Vitesse arbre		Unterkerbung Messerwelle Undercut eye coplio	5700 g/1'	6000 g/1'	6000 g/1'
▶ Apportazione massima Max. cutting depth Maxi prise du bois		Max. Abrtragung Max. aspiration	4	4	4
▶ Potenza motore CV Motor power Puissance moteur CV		Motorstärke Potencia motor CV	3	4	5,5
▶ Piùla a spessore Thick. mesor Dickenleuse Regrustadora	Dim. piena table dim. Dm. table	Tischh. Dim. de la mesa	300x650	410x605	500x800
▶ Spessore max. pialabile Max. thickness capacity Epaisseur max. de rabotage		Max. Hobelhöhe Max. espesor de rugosado	220	220	240
▶ Apportazione massima Max. thickness capacity Epaisseur max. de rabotage		Max. Abrtragung Max. aspiration	4	4	8
▶ Velocità di avanzamento Feed speed Vitesse d'avancement	7 m/1'	Vorwärtsgeschwindigkeit Velocidad de avance	7 m/1'	7 m/1'	7-14 m/1'
▶ Cernitine Mortiseuse Largochabotter Tafelbohrer	Dim. piena Table dim. Dm. table	Tischh. Dim. de la mesa	600x250	420x220	545x280
▶ Escavazione verticale Height adjustment Déplacement vertical		Höhenverstellung Resortido vertical	90	100	170
▶ Seghe circolari Circular saw Säge kreisförmig Sierra circular	Dim. del carrello Carrriage dim. Dm. table roulinerie	Rollschub. Modulos del carro	1250x290	1600x240	1300x290
▶ Dime del piano fisso Fixed table dim. Dim. de la table fixe		Festschub. Dim. de la mesa	1000x220	1100x239	1100x460
▶ a larva sega Saw blade a lame scie		Sägeblatt Durchmesser o disco sierra	250	300	300
▶ a larva incisore (a richiesta) Scoring blade (optional) a lame inciseur (sur demande)		a Vortz (Sonderbohr) a disco Incheor (a pedido)		80	80
▶ Velocità larva sega Saw blade rotation Vitesse lame scie		Sägeblatt-drehgeschwindigkeit Velocidad disco sierra	4000 g/1'	4000 g/1'	4000 g/1'
▶ Motore sega Saw motor power Puissance moteur scie CV	CV HP Potencia motor sierra CV	Sägemotorstärke PS Potencia motor sierra CV	3	4	4
▶ Spindle Spindle a arbre	Spindle ø L'e ø		30	30	30
▶ Giri albero Spindle speed Vitesse arbre	Giri/1' Spindle speed Vitesse arbre	Spindel-drehgeschwindigkeit Velocidad eje topi	4300/6000	3500/6000/8000	
▶ Spostamento verticale albero Vertical spindle stroke Déplacement vertical de l'arbre		Höhenverstellung der Spindel Desplazamiento vertical eje	115	115	140
▶ Apertura sul piano a Table opening Ouvverture dans la table a		Tischöffnung a Agujero en la mesa a	180	210	260
▶ Motore topi Spindle motor Moteur topie CV		Patamotor PS Motor topi CV	3	4	4
▶ Peso Weight Poids kg		Gewicht Peso kg	400	560	1230